

TALL VERSION

CBS 2021

FILTER COFFEE BREWERS

Stylish and Professional Coffee Brewer
for your company



CALIBRATION PANEL WITH LCD

Graphical presentation of programmed options and processes of brewing. Allows easy set up of adjustable parameters:

- > Number of Portions (coffee cups)
- > Brew Time and Temperature
- > Degree of Preliminary Wetting
- > Dripping Delay
- > By-Pass Option
- > Low Temp / No Brew

HOT WATER

Electronically controlled hot water faucet, dispenses hot water based on selected temperature of water in the tank.

PULSE-BREW™ SYSTEM

Guarantees even and full saturation of the coffee bed. You decide whether to select a continuous shower or intermittent surges of water for your roasts.

DISPENSERS

Accommodates Luxus® L3D-05 2 Liter Dispenser.



FETCO®

Driven To Pioneer Innovation™

DIMENSIONS AND SPECIFICATIONS

Standard Electrical Configurations

Model	Code	Heater Configuration kW	Voltage AC	Phase	Wires	KW	Maximum Amp Draw
CBS-2021	E21016X	2x1.7	220 / 240	1	2+ground	3.4	15

Standard Plumbing Configurations / Brewing Efficiency

Water Pressure at	Water Inlet cal	Batches Per Hour	Maximum Efficiency ⁽¹⁾ liters/hour	Brewing Cycle Duration min
1.4-5.5	3/4 (option 1/4)	max 12	25	4

(1). Based on factory settings and water inlet temperature of 20°C.

Dimensions

Dimensions [width/height/depth] mm	Empty / Full Brewer kg	Empty Dispenser kg	Dimensions [width/height/depth] mm	Shipping Weight kg
220 / 690 / 475	8.9 / 18.1	1.9 / 3.8	320 / 810 / 500	12.5

Single Packing Box

ADDITIONAL INFORMATIONS

Accessories

- ▶ D058 2 Liter L3D-05 LUXUS® Thermal Dispenser
- ▶ A128 Iced Tea Brew Basket

Paper Filters

- ▶ F007 11 1/4" x 3 3/4" Paper Filters (500 per case)
- ▶ F003 9 3/4" x 4 1/2" Paper Filters (1000 per case)

MODELS

CBS-2021



CONTACT

Address

Fetco Inc. Sp. z o.o.
Adamowicza 8
Góra Kalwaria 05-530
POLAND

Phone / Fax

+ 48 22 727 4787
+ 48 22 727 4788

Internet / E-Mail

www.fetco.com
info@fetco.com

Dealer