

SERIES

CBS 2050e

FILTER COFFEE BREWERS

Innovative System
for Coffee Brewing



STAINLESS STEEL BODY

Solid appearance and ease of keeping brewer clean.

PULSE-BREW™ SYSTEM

Guarantees of having an even and full saturation of the coffee bed. You decide of whether to select a continuous shower or intermittent surges of water for your roasts.

CALIBRATION PANEL

Tool for easy set up of adjustable parameters:

- > Brew Volume
- > Brew Time
- > By-Pass Option
- > Prewet Time
- > Prewet Delay
- > Water Temperature
- > Low Temp/No Brew

HOT WATER

Electronically controlled hot water faucet with adjustable temperature.

DISPENSERS

Optimization of the performance of brewer by the use of several dispensers with it.



FETCO®

Driven To Pioneer Innovation™

DIMENSIONS AND SPECIFICATIONS

Standard Electrical Configurations / Brewing Efficiency

Model	Heater Configuration kW	Voltage ac	Phase	Wires	KW	Maximum Amp Draw	Batches Per Hour	Maximum Efficiency ⁽¹⁾ liters/hour
CBS205 1e	2x3	230	1	2+ground	5.2	25	10	60
CBS2052 e	2x3	230	1	2+ground	5.2	25	2x10	120
	2x4	230	1	2+ground	6.8	25	2x10	120
	3x3	3x400	3	4+ground	7.7	20	2x11	132
	3x4	3x400	3	4+ground	10.3	25	2x11	132
CBS2052 e 2	2x3	230	1	2+ground	5.2	25	2x10	160
	2x4	230	1	2+ground	6.8	25	2x10	160
	3x3	3x400	3	4+ground	7.7	20	2x11	176
	3x4	3x400	3	4+ground	10.3	25	2x11	176

(1). Based on factory settings and water inlet temperature of 20°C.

Dimensions

Model	Dimensions [W/H/D] mm	Empty / Full Brewer kg	Empty Dispenser kg	Type of dispenser
CBS205 1e	324 / 948 / 505	25 / 46	4.8	L3D15
CBS2052 e	554 / 948 / 512	42 / 81	4.8	L3D15
CBS2052 e 2	554 / 1004 / 512	46 / 85	5.2	L3D20

Single Packing Box

Model	Dimensions [W/H/D] mm	Shipping Weight kg	Water Pressure at	Water Inlet cal
CBS205 1e	380 / 920 / 640	34.0	1.4-5.5	1/2
CBS2052 e	610 / 940 / 640	54.8	1.4-5.5	1/2
CBS2052 e 2	610 / 940 / 640	58.0	1.4-5.5	1/2

Standard Plumbing Configurations

ADDITIONAL INFORMATIONS

Accessories

- ▶ D049 6 Liter L3D15 LUXUS® Thermal Dispenser
- ▶ D050 8 Liter L3D20 LUXUS® Thermal Dispenser
- ▶ D052 6 Liter L3S15 LUXUS® Thermal Dispenser
- ▶ D053 8 Liter L3S20 LUXUS® Thermal Dispenser

- ▶ A097 S3S-15/20-1 Serving Station
- ▶ A098 S3S-15/20-2 Serving Station
- ▶ A099 S3S-15/20-3 Serving Station

Paper Filters

- ▶ 15" x 5" (500 per case)

MODELS

CBS205 1e



CBS2052 e



CBS2052 e 2



CONTACT

Address

Fetco Inc. Sp. z o.o.
Adamowicza 8
Góra Kalwaria 05-530
POLAND

Phone / Fax

+ 48 22 727 4787
+ 48 22 727 4788

Internet / E-Mail

www.fetco.com
info@fetco.com

Dealer