

HWB

HOT WATER BOILERS

Equipment which put high-volume, steaming, hot water at your fingertips – quickly, easily and fast

ELECTRONIC CONTROL

Control panel informs when water reaches programmed temperature (82-98°C).

ISOLATED WATER TANK

Completely isolated water tank guarantees saving of energy and ability of uninterrupted work.

HIGH CAPACITY

High capacity of the water tank allows having high volume of hot water always on demand.

AUTOMATIC REFILL

Ensures high productivity, convenience and safety.

WATER SHUT OFF VALVE

An additional safety precaution from uncontrolled drip out of the water, e.g. during night.

STAINLESS STEEL BODY

Made completely from the polished, acid-proof stainless steel that gives solid appearance and ease of keeping boiler clean.



FETCO[®]

Driven To Pioneer Innovation[™]

DIMENSIONS AND SPECIFICATIONS

Standard Plumbing Configurations

Model	Capacity liter	Efficiency ⁽¹⁾ liters/hour	Flow Rate liters/min	Water Inlet cal	Water Pressure at
HWB 5	18	35	7	1/2	1.4-5.5
HWB 10	38	72	7	1/2	1.4-5.5
HWB 15	57	110	7	1/2	1.4-5.5
HWB 25	95	180	7	1/2	1.4-5.5

(1). Based on factory settings and water inlet temperature of 20°C.

Standard Electrical Configurations

Model	Heater Configuration kw	Voltage ac	Phase	Wires	KW	Max Amp Draw	Fuse A
HWB 5	1x3	230	1	2+ground	2.9	12.2	16
HWB 10	2x3	230	1	2+ground	5.8	24.3	25
HWB 15	3x3	3x400	3	4+ground	8.6	21	20
HWB 25	6x3	3x400	3	4+ground	17.3	42	25

Dimensions

Model	Dimensions [W/H/D] mm	Empty / Full Hot Water Boiler kg	Dimensions [W/H/D] mm	Shipping Weight kg
HWB 5	256 / 752 / 451+150 faucet	25.6 / 43.6	240 / 740 / 630	29.0
HWB 10	412 / 752 / 454+150 faucet	34.0 / 72.0	430 / 790 / 630	38.5
HWB 15	511 / 752 / 560+150 faucet	43.6 / 100.5	530 / 790 / 740	48.0
HWB 25	714 / 756 / 560+150 faucet	57.0 / 152.0	730 / 790 / 740	63.0

Single Packing Box

ADDITIONAL INFORMATIONS

Accessories

- ▶ A039 - In-Line Water Filter MC With Cartridge
- ▶ A075 - Replacement Water Filter Cartridge QL3

MODELS

HWB 5



HWB 10



HWB 15



HWB 25



CONTACT

Address

Fetco Inc. Sp. z o.o.
Adamowicza 8
Góra Kalwaria 05-530
POLAND

Phone / Fax

+ 48 22 727 4787
+ 48 22 727 4788

Internet / E-Mail

www.fetco.com
info@fetco.com

Dealer

HWB 2

HOT WATER BOILERS

Professional Hot Water Boiler
for smaller applications

ELECTRONIC DISPLAY

Allows effortless programming of the desired water temperature (82°-96° C). Indicates current water temperature and alerts when the desired water temperature has been reached.

HIGH-QUALITY COMPONENTS

Ensures durability in a stylish look.

GUARDED FAUCET

Guarded hot water faucet for added protection.

ISOLATED WATER TANK

Completely insulated water tank guarantees efficient use of energy and prevents scalding.

AUTOMATIC REFILL

Ensures continuous flow of water.

REMOVABLE DRIP TRAY

Keeps your serving area spill-free and allows for easy cleaning.



FETCO[®]

Driven To Pioneer Innovation[™]

DIMENSIONS AND SPECIFICATIONS

Standard Plumbing Configurations

Model	Capacity liters	Efficiency ⁽¹⁾ liters/hour	Flow Rate liters/min.	Water Inlet inch	Water Pressure at
HWB-2	7.6	25	5.9	3/4	1.4-5.5

Standard Electrical Configurations

Heater Configuration kw	Voltage ac	Phase	Wires	KW	Maximum Amp Draw
2x1.7	230 / 240	1	2 + ground	3.4	15

(1). Based on factory settings and water inlet temperature of 20°C.

Dimensions

Dimensions [W/H/D] mm	Empty / Full Boiler kg	Dimensions [W/H/D] mm	Shipping Weight kg
220 / 531 / 390	6.7 / 14.3	320 / 650 / 500	9

Single Packing Box

MODELS

HWB-2



CONTACT

Address

Fetco Inc. Sp. z o.o.
Adamowicza 8
Góra Kalwaria 05-530
POLAND

Phone / Fax

+ 48 22 727 4787
+ 48 22 727 4788

Internet / E-Mail

www.fetco.com
info@fetco.com

Dealer